

## Student Result

**Student Name:** Siya Sarfraj Shaikh

**Exam:** Python , Django , Angular Programming

**Score:** 0.0/45.0

**Percentage:** 0.00%

### Question-wise Summary

| Sr.no | Question                                                                        | Selected Answer     | Correct Answer                                                          |
|-------|---------------------------------------------------------------------------------|---------------------|-------------------------------------------------------------------------|
| 1     | Which type of Programming does Python support?                                  | <i>Not Answered</i> | <b>all of the mentioned</b>                                             |
| 2     | What does the @staticmethod decorator do in a Python class?                     | <i>Not Answered</i> | <b>Defines a method that doesn't receive an implicit first argument</b> |
| 3     | In Django, which method is used to create database tables based on your models? | <i>Not Answered</i> | <b>manage.py makemigrations and manage.py migrate</b>                   |

|   |                                                                                                                                                                                                                                                                                                                                                                         |                         |                         |
|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|-------------------------|
| 4 | <p>What will be the output of the following Python code?</p> <pre>def create_multipliers():<br/>    return<br/>    [lambda<br/>    x: i * x for<br/>    i in<br/>    range(4)]<br/>functions<br/>=<br/>create_multipliers()<br/>results =<br/>[f(2) for f<br/>in<br/>functions]<br/>print(results)</pre>                                                                | <p>Not<br/>Answered</p> | <p>[6, 6, 6,<br/>6]</p> |
| 5 | <p>What will be the output of the following Python code?</p> <pre>def create_funcs():<br/>    funcs = []<br/>    for i in<br/>    range(3):<br/>        def f(x,<br/>        i=i):<br/>            return x<br/>            + i<br/>        funcs.append(f)<br/>    return<br/>    funcs<br/>funcs =<br/>create_funcs()<br/>print([f(10)<br/>for f in<br/>funcs])</pre> | <p>Not<br/>Answered</p> | <p>[10, 11,<br/>12]</p> |

|   |                                                                                                                                                                                                                                                                                            |                         |                                                   |
|---|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|---------------------------------------------------|
| 6 | <p>What will be the output of the following Python code?</p> <pre>def logger(func): def wrapper(*args, **kwargs): print(f"Calling {func.__name__}") return func(*args, **kwargs) return wrapper @logger def add(x, y): return x + y result = add(add(1, 2), add(3, 4)) print(result)</pre> | <p>Not<br/>Answered</p> | <p>Calling<br/>add (3<br/>times),<br/>then 10</p> |
|---|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|---------------------------------------------------|

|   |                                                                                                                                                                                                                                                |                         |                |
|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|----------------|
| 7 | <p>What will be the Output of the Following Code?</p> <pre>class Weird: def __init__(self, x): self.x = x def __eq__(self, other): return self.x == other.x a = Weird(10) b = Weird(10) d = {a: "Hello", b: "World"} print(len(d), d[a])</pre> | <p>Not<br/>Answered</p> | <p>2 Hello</p> |
|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|----------------|

|   |                                                                                                                                                                                                                                                         |                     |         |
|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|---------|
| 8 | <p>What will be the Output of the Following Code?</p> <pre>def tricky(n, cache={}): if n in cache: return cache[n] if n &lt;= 1: return 1 cache[n] = tricky(n-1) + tricky(n-2) return cache[n] print(tricky(4)) print(tricky(3)) print(tricky(2))</pre> | <p>Not Answered</p> | 5, 3, 2 |
|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|---------|

|   |                                                                                                                                                                                                                                                                                                                             |                            |                                         |
|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------------|
| 9 | <p>What will be the Output Of the Following Code?</p> <pre>def subgen():<br/>    yield 1<br/>    yield 2<br/>    return 3<br/>def main():<br/>    result =<br/>    yield<br/>    from<br/>    subgen()<br/>    print("Returned:",<br/>    result) g<br/>    = main()<br/>    for val in<br/>    g:<br/>    print(val)</pre> | <p><i>Not Answered</i></p> | <p><b>1, 2,<br/>Returned:<br/>3</b></p> |
|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-----------------------------------------|

|    |                                                                                                                                                                                                                                        |                         |   |
|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|---|
| 10 | <p>What will be the Output of the Following Code?</p> <pre>class Key: def __init__(self, val): self.val = val def __eq__(self, other): return self.val == other.val k1 = Key(1) k2 = Key(1) d = {k1: 'a', k2: 'b'} print(len(d))</pre> | <p>Not<br/>Answered</p> | 2 |
|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|---|

|    |                                                                                                                                                                                                                                                                                          |                     |                                         |
|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|-----------------------------------------|
| 11 | <p>What will be the Output of the Following Code?</p> <pre>def dec1(func): def wrapper(*args): print("dec1") return func(*args) return wrapper def dec2(func): def wrapper(*args): print("dec2") return func(*args) return wrapper @dec1 @dec2 def hello(): print("Hello") hello()</pre> | <p>Not Answered</p> | <p><b>dec1,<br/>dec2,<br/>Hello</b></p> |
|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|-----------------------------------------|



|    |                                                                                                                                                                                                                                                                                                     |                     |                                              |
|----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|----------------------------------------------|
| 12 | <p>What will be the Output of the Following Code?</p> <pre>def sub():<br/>    yield 1<br/>    yield 2<br/>    return "Done"<br/>def<br/>main():<br/>    x = yield<br/>    from sub()<br/>    print("Subgen returned:",<br/>    x)<br/>    g = main()<br/>    for i in g:<br/>        print(i)</pre> | <p>Not Answered</p> | <p>1 2<br/>Subgen<br/>returned:<br/>Done</p> |
| 13 | <p>What will be the Output of the Following Code?</p> <pre>ef func(a,<br/>L=[]):<br/>    L.append(a)<br/>    return L<br/>print(func(1))<br/>print(func(2))<br/>print(func(3))</pre>                                                                                                                | <p>Not Answered</p> | <p>[1], [1,<br/>2], [1, 2,<br/>3]</p>        |

|    |                                                                                                                                                                                                                                                                                       |              |                                              |
|----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|----------------------------------------------|
| 14 | Which of the following operations will NOT trigger model.save() or signals (pre_save/post_save)?                                                                                                                                                                                      | Not Answered | MyModel.objects.bulk_c                       |
| 15 | What will be printed?<br>Component:<br>@Component({<br>selector:<br>'app-test',<br>template:<br>'{{ value<br>}}' })<br>class<br>TestComponent<br>implements<br>OnInit {<br>value =<br>'initial';<br>ngOnInit()<br>{<br>setTimeout()<br>=><br>this.value<br>=<br>'changed',<br>0); } } | Not Answered | Initial                                      |
| 16 | What does providing a service in the component (instead of module) do?                                                                                                                                                                                                                | Not Answered | Creates a new service instance per component |

|    |                                                                                                                                                            |              |                                                    |
|----|------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|----------------------------------------------------|
| 17 | n a Django + Angular app using REST API, what is a good reason to disable CSRF middleware?                                                                 | Not Answered | Angular uses JWT Auth and doesn't send CSRF tokens |
| 18 | If an Angular frontend calls a Django API and receives a CORS error, what should be done?                                                                  | Not Answered | Configure CORS_ORIGIN_ALLOW in Django              |
| 19 | What will be the Output of the Following Code?<br>stack = []<br>for i in range(3):<br>stack.append(i)<br>for i in range(2):<br>stack.pop()<br>print(stack) | Not Answered | [0]                                                |

|    |                                                                                                                                                                                                                         |              |                            |
|----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|----------------------------|
| 20 | <p>What will be the Output of the Following Code? s = "((())"</p> <pre> stack = [] for ch in s:     if ch == '(':         stack.append(ch)     else:         if stack:             stack.pop() print(len(stack)) </pre> | Not Answered | Extra '(' remaining        |
| 21 | <p>During project setup, if ng serve fails with the error "Local workspace file ('angular.json') could not be found", what is the likely issue?</p>                                                                     | Not Answered | Problems with node_modules |
| 22 | <p>In Angular, which file is used to define the set of modules, components, and services?</p>                                                                                                                           | Not Answered | app.module.ts              |

|    |                                                                                                                                                                    |              |                                                                                                                            |
|----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|----------------------------------------------------------------------------------------------------------------------------|
| 23 | <p>What will be the Output of the Following Code?</p> <pre>def f(x, l=[]):     for i in range(x):         l.append(i*i)     return l print(f(3)) print(f(2))</pre> | Not Answered | [0, 1, 4, 0, 1]                                                                                                            |
| 24 | <p>In Angular (<math>\geq 2+</math>), what is the difference between NgModule.imports and NgModule.exports?</p>                                                    | Not Answered | <p><b>imports</b> declares dependencies the module needs, <b>exports</b> makes parts available to other modules</p>        |
| 25 | <p>Which of these is a valid way to lazily load a module in Angular's router (from Angular 8+)?</p>                                                                | Not Answered | <pre>{ path: 'admin',   loadChildren:     () =&gt;     import('./admin/admin.module')     =&gt;     m.AdminModule) }</pre> |

|    |                                                                                                                                                                                                                                                                                                                                                                                                                                |                            |                                        |
|----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|----------------------------------------|
| 26 | <p>Given the following models:</p> <pre>class Author(models.Model):     name = models.CharField(max_length=100) class Book(models.Model):     title = models.CharField(max_length=100)     author = models.ForeignKey(Author,                               on_delete=models.CASCADE,                               related_name='books')</pre> <p>Which of these queries returns all Author instances that have no books?</p> | <p><i>Not Answered</i></p> | <p><b>Author.objects.filter(bo</b></p> |
|----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|----------------------------------------|

|    |                                                                                                                                                                                       |              |                                                                        |
|----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|------------------------------------------------------------------------|
| 27 | What happens when you call save() on a Django model instance without specifying force_insert or force_update, and the instance has a primary key that already exists in the database? | Not Answered | It will do an UPDATE                                                   |
| 28 | In Django REST Framework (DRF), what is the main function of SerializerMethodField?                                                                                                   | Not Answered | It enables custom read-only fields whose value is computed by a method |

|    |                                                                                                          |                     |                                                                                                                              |
|----|----------------------------------------------------------------------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------|
| 29 | Which of the following is the most efficient way to handle a large number of background tasks in Django? | <i>Not Answered</i> | <b>Integrating with a task queue like Celery.</b>                                                                            |
| 30 | How would you implement real-time communication (e.g., chat) in a Django application?                    | <i>Not Answered</i> | <b>Using Django Channels for WebSockets.</b>                                                                                 |
| 31 | What is the primary purpose of ChangeDetectionStrategy.OnPush in Angular?                                | <i>Not Answered</i> | <b>To improve performance by only checking for changes when input properties change or an event is explicitly triggered.</b> |



|    |                                                                                                                                                      |                     |                                                                                                                          |
|----|------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|--------------------------------------------------------------------------------------------------------------------------|
| 32 | How can you ensure proper communication between two unrelated Angular components without a direct parent-child relationship?                         | <i>Not Answered</i> | <b>Utilizing a shared service with a Subject or BehaviorSubject.</b>                                                     |
| 33 | When integrating Django as a backend and Angular as a frontend, what is the recommended approach for handling user authentication and authorization? | <i>Not Answered</i> | <b>Implementing token-based authentication (e.g., JWT) where Django issues tokens and Angular stores and sends them.</b> |

|    |                                                                                                                                                             |                     |                                                                                                              |
|----|-------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|--------------------------------------------------------------------------------------------------------------|
| 34 | <p>What will be the Output of the Following Code?</p> <pre>Python x = 10 def outer_func(): x = 5 def inner_func(): print(x) inner_func() outer_func()</pre> | <i>Not Answered</i> | <b>5</b>                                                                                                     |
| 35 | <p>What is the best data structure to implement a cache with FIFO eviction policy?</p>                                                                      | <i>Not Answered</i> | <b>Queue + HashMap</b>                                                                                       |
| 36 | <p>What is the purpose of csrf_token in a Django form?</p>                                                                                                  | <i>Not Answered</i> | <b>To prevent Cross-Site Request Forgery (CSRF) attacks by ensuring the request comes from your own site</b> |

|    |                                                                           |                     |                                                                                                              |
|----|---------------------------------------------------------------------------|---------------------|--------------------------------------------------------------------------------------------------------------|
| 37 | What is the main advantage of lazy loading feature modules in Angular?    | <i>Not Answered</i> | <b>It allows for loading modules on demand, which reduces the initial application load time.</b>             |
| 38 | What is the main purpose of the RouterModule.forRoot() method in Angular? | <i>Not Answered</i> | <b>To register the routing service and provide the router configuration for the root application module.</b> |

|    |                                                                                  |                     |                                                                                                                                                                                 |
|----|----------------------------------------------------------------------------------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 39 | What is the difference between constructor and ngOnInit in an Angular component? | <i>Not Answered</i> | <b>constructor is for dependency injection and simple initializations, while ngOnInit is for more complex logic that should run after the component's inputs are available.</b> |
| 40 | What does the queryset attribute in a Django generic ListView define?            | <i>Not Answered</i> | <b>The list of objects that the view will display</b>                                                                                                                           |
| 41 | In the context of exception handling, what is the purpose of the finally block?  | <i>Not Answered</i> | <b>It is always executed, regardless of whether an exception occurred or not.</b>                                                                                               |

|    |                                                                           |                     |                                                                                               |
|----|---------------------------------------------------------------------------|---------------------|-----------------------------------------------------------------------------------------------|
| 42 | What does the pass statement do in Python?                                | <i>Not Answered</i> | <b>It acts as a placeholder where code is syntactically required but no action is needed.</b> |
| 43 | How do you pass data from a child component back up to a parent component | <i>Not Answered</i> | <b>B) Using @Output() and an EventEmitter.</b>                                                |
| 44 | In the Django MVT (Model-View-Template) architecture, what is the "T"?    | <i>Not Answered</i> | <b>Template</b>                                                                               |
| 45 | How do you pass data from a parent component to a child component?        | <i>Not Answered</i> | <b>Using the @Input() decorator.</b>                                                          |